



# System Wash

Manufacturers of Quality High Pressure Cleaning Equipment

## *Pulse Range*

The **Pulse** Range has been constructed using the very latest computer aided design and manufacturing systems available. As a result of this technology, all the service and repair parts are very accessible and easy to maintain with no compromise to the striking appearance. The pulse is packed with features normally associated with high - end pressure washers which is why we are confident that our machines represent extremely good value for money

Built onto a heavy gauge thermoplastic chassis with 10" high impact rubber wheels and twin castors (one locking) for durability and stability, **Pulse** features a WRAS approved ball valve and water tank system. The **Pulse** has a removable top and rear cover for service access, a storage area for service spares, an integral chemical tank and a 22 litre fuel tank with low fuel cut out and visual indication for power connection pump on, burner on and low fuel state.





# System Wash

Manufacturers of Quality High Pressure Cleaning Equipment

## Pulse Range

### Motor

All **Pulse** units feature a direct drive four-pole electric motor running at 1400 – 1450 RPM, incorporating squirrel cage rotor construction and a bi-directional cooling fan providing maximum efficiency.

### Boiler

The boiler comprises of a heavy gauge stainless steel jacket, featuring stainless steel upper and lower head assemblies and a stainless steel lower flame break ring and pan. Heat diffusion is maximized by special retained fire resistant pads and deflected around a double wound seamless coil assembly, making this unit compact but highly efficient.

### The fuel system features 3 stage filtration

### Pump

All **Pulse** machines are fitted with top quality industrial pumps featuring a 3-piston ceramic plunger system; long life hardened crankshafts and oil immersed bearing profile. All the wetted parts are constructed of brass or stainless steel ensuring maximum anti corrosion properties. The whole range is equipped with the unique **F.S.A. System**. This comprises of a special flow sensitive automatic Regulator, which ensures no pressure remains trapped in the high-pressure line during bypass operation or shut down mode. Low voltage controls (24v) have been fitted as standard to achieve maximum operator safety, complemented by a fully automated, timed total shut down system, and thermal overload protection for motor and boiler, low-level fuel cut off is standard on all **Pulse** models.

**Pulse** machines are superb, providing long-term reliability, durability and optimum performance; an investment that will serve you for many years to come.

Model No	Pressure	Flow	Temp	Power	Run Load		RPM	Dimensions	Weight
	Bar	LPM	Deg C	Volts	Amps	Kw		L = 920	Kilos
Pulse 100	90	12.5	80	230V	13	2.5	1450	W = 610	105
								H = 850	

All **Pulse** Machines are Supplied complete with 9 Metres of quality high pressure hose, heavy duty trigger gun and 900mm lance.

Local Dealer

### Connections

Inlet: 1/2" and 3/4" hose tail - Quick release at front  
Outlet: Quick release at front  
Power: 5 Metres Cable at rear  
Chemical: Integral tank 10 litres fill at top  
Fuel Tank: 22 Litres - fill at front