

# System Wash

Manufacturers of Quality High Pressure Cleaning Equipment

## Verso Range

The **Verso** Range has been designed using the very latest computer aided and manufacturing systems available. As a result of this technology all the service and repair parts are very accessible and easy to maintain with no compromise to the striking appearance. The **Verso** is packed with features making it a true high-end pressure washer, which is why we say that our machines represent extremely good value for money.

Built onto a heavy gauge steel powder-coated chassis with 4 x 10 inch high impact rubber wheels for durability and stability; **Verso** features a huge 15 litre 304 grade stainless steel water tank with high-flow ball valve.

The Machine has a secure but removable cover for service access and an 18.5 litre fuel tank featuring low fuel cut-out that shuts down the burner ensuring no damage occurs to the fuel system and shows a visual warning light.






# System Wash

Manufacturers of Quality High Pressure Cleaning Equipment

## Verso Range

### Motor

All **Verso** units feature a direct drive four-pole electric motor running at 1400 – 1450 RPM, incorporating squirrel cage rotor construction and bi-directional cooling fan providing maximum efficiency.

### Boiler

The boiler comprises of a heavy gauge epoxy powder coated jacket, featuring stainless steel upper and lower head assemblies and a stainless steel lower flame break ring. Heat diffusion is maximized by a retained fire cement bottom and deflected around a double wound seamless coil, making this unit compact but highly efficient

### Pump

All **Verso** machines are fitted with top quality industrial pumps featuring a 3-piston ceramic plunger system; long life hardened crankshafts and oil immersed bearing profile. All the wetted parts are constructed of brass or stainless steel ensuring Maximum anti corrosion properties.

The whole range is equipped with the unique **F.S.A. System**. This comprises of a special flow sensitive Regulator, which ensures no pressure, remains trapped in the high-pressure line during bypass operation or shut down mode. Low voltage controls (24v) have been fitted as standard to achieve maximum operator safety, complemented by a fully automated, timed total shut down system, and thermal overload protection for motor and boiler, Low-level fuel cut off is standard on all **Verso** models.

**Verso** machines are superb, providing long-term reliability, durability and optimum performance, an investment that will serve you for many years to come.

Model No	Pressure	Flow	Temp	Power	Run Load		RPM	Dimensions	Weight
	Bar	LPM	Deg C	Volts	Amps	Kw			Kilos
Verso 1	90	12.5	80	230V	13	2.3	1450	L = 1000 W = 680 H = 840	165
Verso 2	180	15	75	400V	3 x 12	5.6	1450		170

All **Verso** Machines are Supplied complete with 9 Metres of quality high pressure hose, heavy duty trigger gun and 900mm lance.

### Connections

Inlet: 1/2" and 3/4" hose tail - Quick release at front  
 Outlet: Quick release at Side  
 Power: 6 Metres Cable at front  
 Chemical: 1.5 Metres 1/4" pipe at front  
 Fuel Tank: 18.5 Litres - fill at front

Local Dealer

